



**HHXX.EX15226
Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze**

Page Bottom

Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

See General Information for Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

SIAM FITTINGS CO LTD
100/1-100/2 MOO 2 SETTAKIT 1 RD
KRATHUMBAN
OMNOI
SAMUT SAKHON, 74130 THAILAND

EX15226

Malleable Iron Fittings, ASME B 16.3 Class 150 (threads manufactured in accordance with ANSI B 1.20.1)

Model/Fig.	Configuration	Size (in.)	Rated Pressure (psig)
AL 90, AL 45, ASL 90, AT, ACR, ACA	90° Elbows, 45° Elbows, 90° Street Elbows, Tees, Crosses, Caps	1/8 - 6	300
ASL 45, AS	45° Street Elbows, Couplings	1/8 - 4	300
AST	Service Tees	1/2 - 2	300
ARCR	Reducing Crosses	1-1/2x1-1/4 - 2x1-1/4	300
ARL	Reducing Elbows	1/4x1/8 - 4x3	300
ART	Reducing Tees	1/4x1/8 - 2-1/2x2x2-1/2	300
ARS	Reducing Couplings	1/4x1/8 - 4x3	300

Malleable Iron Fittings, ASME B 16.14 Class 150 (threads manufactured in accordance with ANSI B 1.20.1)

Model/Fig.	Configuration	Size (in.)	Rated Pressure (psig)
AP	Plugs	1/8 - 3	300
ALN	Locknuts	1/8 - 4	300
ABU	Bushings	1/4x1/8 - 6x5	300

Malleable Iron Fittings, ASME B 16.3 Class 300 (threads manufactured in accordance with ANSI B 1.20.1)

Model/Fig.	Configuration	Size (in.)	Rated Pressure (psig)
AXHL 90, AXHL 45, AXHSL 90, AXHS, AXHT, AXHCA	90° Elbows, 45° Elbows, 90° Street Elbows, Tees, Couplings, Caps	1/4 - 1	2000
AXHL 90, AXHL 45, AXHSL 90, AXHS, AXHT, AXHCA	90° Elbows, 45° Elbows, 90° Street Elbows, Tees, Couplings, Caps	1-1/4 - 2	1500
AXHL 90, AXHL 45, AXHS, AXHT, AXHCA	90° Elbows, 45° Elbows, Tees, Couplings, Caps	2-1/2 - 3	1000
AXHRS	Reducing Couplings	1/2x1/4 - 1x3/4	2000
AXHRS	Reducing Couplings	1-1/4x1/2 - 2x1-1/2	1500
AXHRS	Reducing Couplings	2-1/2x1-1/2 - 3x2-1/2	1000
AXHRT	Reducing Tees	3/4x3/4x1/2 - 1x1x3/4	2000
AXHRT	Reducing Tees	1-1/4x1-1/4x1/2 - 2x2x1-1/2	1500
AXHRT	Reducing Tees	2-1/2x2-1/2x2 - 3x3x2	1000

Bronze Fittings, ANSI/ASME B 16.15 Class 125 (threads manufactured in accordance with ANSI B 1.20.1)

Model/Fig.	Configuration	Size (in.)	Rated Pressure (psig)
CL 90, CL 45, CS, CT, CCA	90° Elbows, 45° Elbows, Coupling, Tees, Caps	1/8 - 4	200
CSL 90, CSL 45	90° Street Elbows, 45° Street Elbows	1/8 - 2	200
CCR	Crosses	1/8 - 2-1/2	200
CRT	Reducing Tees	1/4x1/8 - 1-1/2x1-1/4x1-1/4	200
CRL 90	90° Reducing Elbows	1/4x1/8 - 1-1/4x1	200

Bronze Fittings, ANSI/ASME B 16.15 Class 250 (threads manufactured in accordance with ANSI B 1.20.1)

Model/Fig.	Configuration	Size (in.)	Rated Pressure (psig)
CXL 90, CXT, CXS	90° Elbows, Tees, Couplings	1/4 - 3	400
CXL 45	45° Elbows	1/2 - 2	400
CXCR	Crosses	1/4 - 2	400

Last Updated on 2008-02-14

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2009 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

